

SAP Free Water Barriers for Aviation Fuel

CDF-X™ Series
2" OD EI 1588 Qualified Water Barrier
Elements for Aviation Fuel Filtration



Next Generation Barrier Elements:

Since the introduction of aviation fuel monitor cartridges in aviation fueling, super absorbent polymers (SAP) have been the essential materials used in the final stage of airport ground fueling systems for protection of on-board systems from water contamination. The material's ability to absorb and chemically lock in water have it's challenges—potential media migration downstream.

Parker Velcon SAP Free water barrier technology eliminates the uncertainty of SAP migration downstream by removing SAP from the equation while still providing the efficiency and water removing performance you can rely on from a fuel monitor cartridge.



CDFX

Pending

- **Completion of Field Trials for A4A/JIG acceptance**

Contact Information:

Parker Hannifin Corporation
Aerospace Filtration Division
1210 Garden of the Gods Rd.
Colorado Spring, CO 80907

phone +1 719 5315855
fax +1 719 5315690
vfsales@parker.com

www.parker.com | www.velcon.com

Product Features:

- **INNOVATIVE BARRIER TECHNOLOGY**
Water and dirt are prevented from bypassing downstream allowing only clean dry fuel
- **PERFORMANCE TO MEET CURRENT EI SPECIFICATIONS**
Defense against emulsified water and full slug protection
- **COST AND RESOURCE EFFICIENT**
Fits currently deployed monitor housings without the need for costly retrofitting or addition of electronic sensors
- **NO MORE MEDIA MIGRATION CONCERNS**
Zero uncertainties about SAP media migration or extrudables downstream and in filtration systems
- **COMPATIBLE MATERIALS**
Utilizes industry known materials of construction (nylon, PTFE and urethane)



ENGINEERING YOUR SUCCESS.

Surface/Barrier Technology

The new surface/barrier technology provides a drop-in solution for current 2" diameter filter monitors. Exterior dimensions and endcap styles remain the same while media technology are exchanged with new barrier technology. This allows for use with current monitor housings without the need for expensive and costly retrofitting of filtration systems on fuel carts and fueling trucks.

Our barrier technology is:

- Effective against low-water emulsions
- Effective against total water submersion
- Effective when introduced to water slugs at or greater than 101.5 psid (7 bar)

- Effective in fuel with FSII (anti-icing additive)
- Extreme dirt efficiency

HOW OUR NEW BARRIER TECHNOLOGY WORKS

Like a microfilter, our barrier technology filters and prevents water from bypassing downstream

- Water droplets are blocked by a hydrophobic material that is porous to clean, dry fuel.
- Water droplets impeded on the surface of the media coalesce and drop to the bottom of the vessel.

A drop-in solution for current 2" filter monitors.



Filter Element Selection

Cartridge Flow Rate USGPM	Velcon Model Number	Overall Length (in.)	Replacements for:	
			Facet Model Number	Faudi Model Number
5	CDFX-205A	5 13/16"	FG-205-7	M.2-134/6B
10	CDFX-210A	10 13/16"	FG-210-7	M.2-261/6B
15	CDFX-215A	15 13/16"	FG-215-7	M.2-387/6B
20	CDFX-220A	20 13/16"	FG-220 -7	M.2-515/6B
25	CDFX-225A	25 13/16"	FG-225-7	M.2-642/6B
30	CDFX-230A	30 13/16"	FG-230-7	M.2-770/6B