

Features

- · Continuous flow, no shutdown for basket cleaning
- Compact butterfly valve design
- Quick opening covers
- · Convoluted design baskets
- Threaded drain
- Perforated or mesh stainless steel baskets
- Vent
- Positive shutoff

Options

- Ductile iron construction
- Basket perforations from ¹/₃₂" to ¹/₂"
- Basket mesh of 20, 40 or 60
- MONEL® baskets
- Vent valves
- Drain valves
- Gauge taps 1/4" NPT
- Pressure differential gauge and switch connections
- Magnetic basket inserts

MONEL® is a registered trademark of Special Metals Corporation group of Companies.



The butterfly valve advantage

The Eaton Model 52 duplex strainer's design large size with high flow rates benefit from a set of synchronized, high-quality, butterfly valves that minimize the effort to switch the flow from one basket chamber to the other.

The valve replaces the diverter plug used on smaller size strainers and gives a straight flow pattern with no sudden changes in flow direction. The result is a very low pressure loss. A 10" strainer of this type can handle 2,000 gpm (454 m³/h) of water with a pressure drop of only 2 psi (0.14 bar). This is the strainer to choose for high flow rate applications when a low-pressure loss is critical.

Unique basket design

The Model 52 incorporates a larger screening area by convoluting (pleating) the perforated sheet in the strainer basket, thus increasing the available screening area while reducing the total basket size.

The flow enters the basket from the side, not the top, resulting in a straight through flow pattern. This means a lower pressure drop and greater time between basket cleanings than would be possible with standard design baskets—a substantial savings in time and operating

Compact design

Lighter weight and a smaller profile make this strainer ideal for situations when space requirements are tight.

Easy to operate


- A single hand wheel operator can be on either side of the strainer if accessibility is a problem.
- An arrow on the top of the gear housing indicates which basket chamber is in service and which is ready for cleaning.
- Quick opening covers make strainer basket changing or cleaning quick and easy with no tools or lifting gear.

Model 52 Large Duplex Basket Strainer

Selection chart

Size	Material	End connection	Seals	Pressure rating*
10" to 12"	Iron	Flanged 125#	Buna-N®	200 psi (13.8 bar)
10" to 12"	Bronze	Flanged 150#	Buna-N	200 psi (13.8 bar)
14" to 18"	Iron	Flanged 125#	Buna-N	150 psi (10.3 bar)
14" to 18"	Bronze	Flanged 150#	Buna-N	150 psi (10.3 bar)

^{* @ 100 °}F (38 °C)




Cy factors*

Size	Value	Size V	alue
10"	1300	16" 3	400
12"	2000	18" 4	900
14"	2900		

^{*} For water with clean, perforated basket

Dimensions and weights are for reference only. Contact Eaton for certified drawings.



Dimensions (in/mm)

D	.0.00	····/ ·····	,																
Pipe size	A	В	C	D	E	F	G	Н	J	К	L	М	N	Р	Q	R	s	Wt (I Iron	lb / <mark>kg</mark>) Bronze
10	45	51	26	52	22-1/2	19	32	30-1/4	18	12 -3/16	29	49	1-1/2	1/2	1	1	1/4	1600	2003
	1143	1295	660	1321	572	483	813	768	457	310	737	1245	-		32	32	-	727	910
12	62	64	32	66	31	23	41	36- ⁵ /8	16	16- ³ /4	38	66	1-1/2	1/2	1	1	1/4	2650	3318
12	1574	1626	813	1676	787	584	1041	924	406	425	965	1676	-		32	32	-	1205	1508
14	72	76	38	79	35-1/2	27	48	44-3/4	24	18- ³ /4	44-1/2	77	1- ¹ /2	1/2	1	1	1/4	4300	5384
14	1829	1930	965	2007	902	686	1219	1137	610	476	1130	196	_		32	32	_	1955	2447
16	72	76	38	79	35-1/2	27	48	44-3/4	24	18-3/4	44-1/2	77	1-1/2	1/2	1	1	1/4	4400	5509
16	1829	1930	965	2007	902	686	1219	1137	610	476	1130	196	_		32	32	_	2000	2504
10	72	76	38	79	35-1/2	27	48	44-3/4	24	18-3/4	44-1/2	77	1-1/2	1/2	1	1	1/4	4600	_
18	1829	1930	965	2007	902	686	1219	1137	610	476	1130	196	_		32	32	_	2087	_

North America 44 Apple Street

Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America only) Tel: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2 53947 Nettersheim, Germany Tel: +49 2486 809-0

Friedensstraße 41 68804 Altlußheim, Germany Tel: +49 6205 2094-0

An den Nahewiesen 24 55450 Langenlonsheim, Germany Tel: +49 6704 204-0

China No. 3, Lane 280, Linhong Road Changning District, 200335 Shanghai, P.R. China Tel: +86 21 5200-0099

Singapore 100G Pasir Panjang Road #07-08 Singapore 118523 Tel: +65 6825-1668

Av. Ermano Marchetti, 1435 -Água Branca, São Paulo - SP, 05038-001, Brésil Tel: +55 11 3616-8461

For more information, please email us at filtration@eaton.com or visit www.eaton.com/filtration

© 2020 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete. since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.



EF-SSEA-1 10-2020