




**EPSITRON® IP67 POWER**  
No Enclosure Required




# EPSITRON® IP67 Power

## No Enclosure Required




### Universal Supply

- Wide input voltage range: 90 ... 265 VAC
- Suitable for worldwide use
- Active Power Factor Correction eliminates interference from other devices powered by the same source
- Up to 92.4% efficiency reduces energy loss



### Protection from Overload Damage

- PowerBoost provides 150% of output power for four seconds
- Advantageous during start-up or switching of capacitive loads (e.g., valve clusters, motors)
- Power reserve eliminates expensive oversizing




### Temperature Ratings

- -40 °C ... +60 °C at 4 A
- -40 °C ... +70 °C at 2.4 A, derating at +60 °C
- Storage temp. of -40 °C ... +85 °C



### Excellent Protection

- IP67 protection (water and dust)
- Temporary immersion (30 minutes at 1 meter)
- Tamper-proof
- Withstand EMC tested to EN 61204-3
- Protection from overload damage (constant current mode)



### Clear Indication

- LED for clear status indication
- Green (DC OK), red (error)



### Slim Design and Versatile Mounting Options

- Built-in mounting brackets for both vertical and horizontal mounting

[www.wago.com/787-6716](http://www.wago.com/787-6716)

787-6716	Accessories	Part Number	Description
<p>141 mm 54 mm 111 mm</p> <p>EPSITRON® IP67 Power Supply</p> <p>Input: 90 ... 265 VAC/DC</p> <p>Output: 24 VDC / 4 A</p>		787-6716/9500-0000	5 pole 7/8" connector - straight male
		787-6716/9700-0000	5 pole 7/8" connector - straight female
		787-6716/9300-0000	3 pole 7/8" connector - straight female
		787-6716/9100-0000	3 pole 7/8" connector - straight male
		787-6716/9600-0000	5 pole 7/8" connector - right angle male
		787-6716/9800-0000	5 pole 7/8" connector - right angle female
		787-6716/9400-0000	3 pole 7/8" connector - right angle female
		787-6716/9000-1000	3 pole 7/8" connector - T-connector
		767-6716/9310-0030	3 pole 7/8" straight female cable, flying leads, 3 m
		787-6716/9310-0050	3 pole 7/8" straight female cable, flying leads, 5 m
		787-6716/9310-0100	3 pole 7/8" straight female cable, flying leads, 10 m
		787-6716/9510-0015	5 pole 7/8" straight male cable, flying leads, 1.5 m
		787-6716/9510-0030	5 pole 7/8" straight male cable, flying leads, 3 m
		787-6716/9510-0050	5 pole 7/8" straight male cable, flying leads, 5 m